


17" Resistive touchscreen monitor



Unit : mm

Dimensions - I/O View :

- A - Supply connector
- B - USB (touch reserved)
- C - DVI-D
- D - VGA
- E - USB 2.0 (frontal port reserved)
- F - OSD KEYBOARD



DISPLAY	
TFT TYPE	17" TFT LCD
MAX RESOLUTION	1280x1024
LUMINANCE	250 cd/m ²
CONTRAST RATIO	1000 : 1
VIEW ANGLE	85° / 85° / 80° / 80° (L/R/U/D)
MAX COLORS	16.7 Millions
TOUCH TYPE	Five wire resistive

EXTERNAL I/O	
USB PORTS	1x USB 2.0 on front panel
VIDEO INPUT	1x VGA connector, 1x DVI-D connector
SUPPLY CONNECTION	24 VDC terminal block 110-230 VAC standard VDE connector

POWER SYSTEM	
RATED INPUT VOLTAGE	24 VDC 110-230 VAC
INPUT VOLTAGE LIMIT	22-32 VDC 90-264 VAC
POWER CONSUMPTION	16 W

MECHANICAL	
DIMENSION	455x355x63 mm (18x14x2.5 in)
WEIGHT	4.5 Kg
FRONT PANEL	Anodized aluminum
CHASSIS	SECC steel (galvanized)
MOUNTING TYPE	Panel mounting with retaining clips or VESA 100

ENVIRONMENT	
OPERATING TEMPERATURE	0 ~ 50 °C (32 ~ 122 °F)
STORAGE TEMPERATURE	-20 ~ 60 °C (-4 ~ 140 °F)
OPERATING HUMIDITY	10 ~ 95 % @ 40°C (non-condensing)
FRONT PANEL PROTECTION	IP66
EMC	CE
SAFETY	CE

17" Resistive touchscreen monitor

FRONTAL PANEL OPTIONAL

Frontal panel graphic customization area for logo¹

¹To go on with the frontal panel customization, we need the vectorial logo and the logo spot on the panel. Later we will send you a preview to be confirmed.

Unit : mm

