

PVG216-FD



Fanless 15.6" Industrial VESA PC with Intel® N150 / Intel® N97



FEATURES

- Intel® N150 / Intel® N97
- 15.6" 1366x768 / 1920x1080 LCD display
- Projected capacitive multi-touch control
- IP30-compliant
- Dual 2.5 Gigabit Ethernet
- Triple display support
- Wide DC power range 12-36 VDC
- Wide AC power range 85-264 VAC



SYSTEM

CPU	Intel® N150, QC, 3.6 GHz Intel® N97, QC, 3.6 GHz
CHIPSET	Intel® Alder Lake
GRAPHICS	Intel® UHD Graphics
MEMORY TYPE	1x DDR5 SO-DIMM 4800 MHz max 16 GB
AUDIO	Realtek® ALC897
ETHERNET	2x Intel® I226V 2.5 GbE (N150) 2x Intel® I225V 2.5 GbE (N97)

DISPLAY

TFT TYPE	15.6" TFT LCD
MAX RESOLUTION	1366x768 or 1920x1080
LUMINANCE	300 cd/m ² or 500 cd/m ²
CONTRAST RATIO	500 : 1 or 1000:1
VIEW ANGLE	80° / 80°/80° / 80° or 89°/89°/89°/89° (L/R/U/D)
MAX COLORS	16.7 Millions
TOUCH TYPE	Projected capacitive multi-touch control

STORAGE

DEVICE	1x 2.5" SSD
--------	-------------

EXTERNAL I/O

SERIAL PORTS	1x COM (RS-232/422/485) 1x COM (RS-232/422/485) optional 2x COM (RS-232) optional
USB PORTS	2x USB 3.2, 2x USB 2.0
AUDIO	1x Line-Out
VIDEO OUTPUT	2x HDMI (4096x2160)
LAN	2x RJ45 Ethernet ports
PS2	N/A
SUPPLY CONNECTION	24 VDC terminal block 110-230 VAC standard VDE connector

EXPANSION SLOT

MINI-PCIE	1x full size with PCIe x1
M.2	1x Key E (2230), 1x Key M (2280) with PCIe x2

OS SUPPORT

MICROSOFT®	Windows 10 Enterprise LTSC 2021 (64 bit)
MICROSOFT®	Windows 10 PRO (64 bit)
MICROSOFT®	Windows 11 Enterprise LTSC 2024 (64 bit)
MICROSOFT®	Windows 11 PRO (64 bit)
LINUX	Ubuntu 24.04.1 LTS or newer and further distros

POWER SYSTEM

RATED INPUT VOLTAGE	24 VDC 110-230 VAC
INPUT VOLTAGE LIMIT	12-36 VDC 85-264 VAC
POWER CONSUMPTION	50 W

MECHANICAL

DIMENSION (WxHxD)	397x247x85 mm (15.6x9.7x3.3 in)
WEIGHT	6 Kg
FRONT PANEL	Aluminum frontal frame with 3 mm temperate glass
CHASSIS	Black painted steel
MOUNTING TYPE	VESA mount 100

ENVIRONMENT

OPERATING TEMPERATURE	0 ~ 50 °C (32 ~ 122 °F)
STORAGE TEMPERATURE	-20 ~ 60 °C (-4 ~ 140 °F)
OPERATING HUMIDITY	10 ~ 95 % @ 40 °C (non-condensing)
PROTECTION GRADE	IP30
EMC	CE
SAFETY	CE


PVG216-FD



Fanless 15.6" Industrial VESA PC with Intel® N150 / Intel® N97

Dimensions - I/O View :

- A - Power switch
- B - Supply connector
- C - 2x USB 2.0
- D - 2x USB 3.2
- E - 2x HDMI
- F - 2.5 Gigabit LAN 1
- G - 2.5 Gigabit LAN 2
- H - Audio output
- J - Gigabit LAN 3 (optional)
- K - RS-232 (COM 4 - optional)
- L - RS-232 (COM 3 - optional)
- M - RS-232/422/485 (COM 2-optional)
- N - RS-232/422/485 (COM 1)
- O - Wi-fi antenna (optional)



AVAILABLE OPTIONS		CONFIGURATION NUMBER						
		1	2	3	4	5	6	7
WIFI Lan	Wi-Fi Lan ¹	●			●	●		●
LAN	1x RJ45 Gigabit Lan MiniPCI-Express card		●		●		●	●
Serial Ports	1x serial ports RS 232/422/485 and 2 RS 232(DB9)			●		●	●	●
Notes								
¹ 1 mt Wi-Fi antenna cable extension available on request								

PVG216-FD



Fanless 15.6" Industrial VESA PC with Intel® N150 / Intel® N97

FRONTAL PANEL OPTIONAL

Frontal panel graphic customization area for logo¹

¹ To go on with the frontal panel customization, we need the vectorial logo and the logo spot on the panel.
Later we will send you a preview to be confirmed.

