PSR116-FD

Fanless 15.6” Industrial Panel PC with Intel® N150 / Intel® N97



FEATURES

- Intel® N150 / Intel® N97
- 15.6" 1366x768 / 1920x1080 LCD display
- Resistive touch
- Front panel, IP66-compliant
- Dual 2.5 Gigabit Ethernet
- Triple display support
- Wide DC power range 12-36 VDC
- Wide AC power range 85-264 VAC

SYSTEM	
CPU	Intel® N150, QC, 3.6 GHz Intel® N97, QC, 3.6 GHz
CHIPSET	Intel® Alder Lake
GRAPHICS	Intel® UHD Graphics
MEMORY TYPE	1x DDR5 SO-DIMM 4800 MHz max 16 GB
AUDIO	Realtek® ALC897
ETHERNET	2x Intel® I226V 2.5 GbE (N150) 2x Intel® I225V 2.5 GbE (N97)

DISPLAY	
TFT TYPE	15.6” TFT LCD
MAX RESOLUTION	1366x768 or 1920x1080
LUMINANCE	300 cd/m^2 or 500 cd/m^2
CONTRAST RATIO	500 : 1 or 1000:1
VIEW ANGLE	80°/ 80°/80°/ 80° or 89°/89°/89°/89° (L/R/U/D)
MAX COLORS	16.7 Millions
TOUCH TYPE	Five wire resistive

STORAGE	
DEVICE	1x 2.5” SSD

EXTERNAL I/O	
SERIAL PORTS	1x COM (RS-232/422/485) 1x COM (RS-232/422/485) optional 2x COM (RS-232) optional
USB PORTS	2x USB 3.2, 2x USB 2.0
AUDIO	1x Line-Out
VIDEO OUTPUT	2x HDMI (4096x2160)
LAN	2x RJ45 Ethernet ports
PS2	N/A
SUPPLY CONNECTION	24 VDC terminal block 110-230 VAC standard VDE connector

EXPANSION SLOT	
MINI-PCIE	1x full size with PCIe x1
M.2	1x Key E (2230), 1x Key M (2280) with PCIe x2

OS SUPPORT	
MICROSOFT ®	Windows 10 Enterprise LTSC 2021 (64 bit)
MICROSOFT ®	Windows 10 PRO (64 bit)
MICROSOFT ®	Windows 11 Enterprise LTSC 2024 (64 bit)
MICROSOFT ®	Windows 11 PRO (64 bit)
LINUX	Ubuntu 24.04.1 LTS or newer and further distros

POWER SYSTEM	
RATED INPUT VOLTAGE	24 VDC 110-230 VAC
INPUT VOLTAGE LIMIT	12-36 VDC 85-264 VAC
POWER CONSUMPTION	50 W

MECHANICAL	
DIMENSION (WxHxD)	430x275x95 mm (16.9x10.8x3.7 in)
WEIGHT	7 Kg
FRONT PANEL	Anodized aluminum
CHASSIS	SECC steel (galvanized)
MOUNTING TYPE	Panel mounting with retaining clips


ENVIRONMENT	
OPERATING TEMPERATURE	0 ~ 50 °C (32 ~ 122 °F)
STORAGE TEMPERATURE	-20 ~ 60 °C (-4 ~ 140 °F)
OPERATING HUMIDITY	10 ~ 95 % @ 40°C (non-condensing)
FRONT PANEL PROTECTION	IP66
EMC	CE
SAFETY	CE

PSR116-FD

Fanless 15.6” Industrial Panel PC with Intel® N150 / Intel® N97

Dimensions - I/O View :

- **A** - Power switch
- **B** - Remote power On/Off (optional) Remote reset (optional)
- **C** - Wi-fi antenna (optional)
- **D** - RS-232 (COM 4 - optional)
- **E** - RS-232 (COM 3 - optional)
- **F** - RS-232/422/485 (COM 2 - optional)
- **G** - RS-232/422/485 (COM 1)
- **H** - Gigabit LAN 3 (optional)
- **J** - Audio output
- **K** - 2.5 Gigabit LAN 2
- **L** - 2.5 Gigabit LAN 1
- **M** - 2x HDMI
- **N** - 2x USB 3.2
- **O** - 2x USB 2.0
- **P** - 2x USB 2.0
- **Q** - Supply connector
- **R** - Removable CFast (optional)
- **S** - Removable SSD (optional)



Unit : mm

AVAILABLE OPTIONS		CONFIGURATION NUMBER						
		1	2	3	4	5	6	7
WIFI Lan	Wi-Fi Lan[1]	●		●				
LAN	1x RJ45 Gigabit Lan MiniPCI-Express card		●	●				
Notes								
[1] 1 mt Wi-Fi antenna cable extension available on request								

PSR116-FD

Fanless 15.6” Industrial Panel PC with Intel® N150 / Intel® N97

FRONTAL PANEL OPTIONAL
Frontal panel graphic customization area for logo[1]
[1] To go on with the frontal panel customization, we need the vectorial logo and the logo spot on the panel. Later we will send you a preview to be confirmed.

Unit : mm

