

PSR124-FE



Fanless 23.8" Industrial Panel PC with Intel® Ultra5



FEATURES

- Intel® Core™ Ultra5
- 23.8" 1920x1080 LCD display
- Resistive touch
- Front panel, IP66-compliant
- 1x Gigabit Ethernet, 1x 2.5 Gigabit Ethernet
- Triple display support
- Wide DC power range 12-36 VDC
- Wide AC power range 85-264 VAC




SYSTEM	
CPU	Intel® Core™ Ultra5, 125H
CHIPSET	Intel® Meteor Lake-H
GRAPHICS	Intel® Arc™ Graphics
MEMORY TYPE	1x DDR5 SO-DIMM 5600 MHz max 48 GB
AUDIO	Realtek® ALC256 HD
ETHERNET	1x Intel® I226LM 2.5 GbE 1x Intel® I210AT 1 GbE
DISPLAY	
TFT TYPE	23.8" TFT LCD
MAX RESOLUTION	1920x1080
LUMINANCE	450 cd/m ²
CONTRAST RATIO	1000 : 1
VIEW ANGLE	85° / 85° / 85° / 85° (L/R/U/D)
MAX COLORS	16.7 Millions
TOUCH TYPE	Five wire resistive
STORAGE	
DEVICE	1x 2.5" SSD
EXTERNAL I/O	
SERIAL PORTS	1x COM (RS-232/422/485) 2x COM (RS-232/422/485) optional
USB PORTS	2x USB 3.2, 2x USB 3.2 Type-C, 2x USB 2.0
AUDIO	N/A
VIDEO OUTPUT	1x HDMI (4096x2160), 1x DisplayPort (4096x2160)
LAN	2x RJ45 Ethernet ports
PS2	N/A
SUPPLY CONNECTION	24 VDC terminal block 110-230 VAC standard VDE connector

OS SUPPORT	
MICROSOFT ®	Windows 10 Enterprise LTSC 2021 (64 bit)
MICROSOFT ®	Windows 10 PRO (64 bit)
MICROSOFT ®	Windows 11 Enterprise LTSC 2024 (64 bit)
MICROSOFT ®	Windows 11 PRO (64 bit)
LINUX	Ubuntu 24.04.1 LTS or newer and further distros
POWER SYSTEM	
RATED INPUT VOLTAGE	24 VDC 110-230 VAC
INPUT VOLTAGE LIMIT	12-36 VDC 85-264 VAC
POWER CONSUMPTION	55 W
MECHANICAL	
DIMENSION (WxHxD)	640x402x90 mm (25.2x15.8x3.5 in)
WEIGHT	10 Kg
FRONT PANEL	Anodized aluminum
CHASSIS	SECC steel (galvanized)
MOUNTING TYPE	Panel mounting with retaining clips
ENVIRONMENT	
OPERATING TEMPERATURE	0 ~ 50 °C (32 ~ 122 °F)
STORAGE TEMPERATURE	-20 ~ 60 °C (-4 ~ 140 °F)
OPERATING HUMIDITY	10 ~ 95 % @ 40°C (non-condensing)
FRONT PANEL PROTECTION	IP66
EMC	CE
SAFETY	CE

Fanless 23.8" Industrial Panel PC with Intel® Ultra5

Dimensions - I/O View :

- A - Power switch
- B - Remote power On/Off (optional)
- C - Remote reset (optional)
- D - 2x Wi-fi antenna (optional)
- E - 2x USB 3.2
- F - 1x DisplayPort
- G - RS-232/422/485 (COM 5 - optional)
- H - RS-232/422/485 (COM 4 - optional)
- J - RS-232/422/485 (COM 3)
- L - 2x USB 2.0
- M - Gigabit LAN 2
- N - Gigabit 2.5 LAN 1
- O - 1x HDMI
- P - 2x USB 3.2 (Type-C)
- Q - Supply connector
- R - Removable CFast (optional)
- S - Removable SSD (optional)



AVAILABLE OPTIONS		CONFIGURATION NUMBER						
		1	2	3	4	5	6	7
WiFi Lan	Wi-Fi Lan ¹	●						
Notes								
¹ 1mt Wi-Fi antenna cable extension available on request								

FRONTAL PANEL OPTIONAL	
Frontal panel graphic customization area for logo ¹	
¹ To go on with the frontal panel customization, we need the vectorial logo and the logo spot on the panel. Later we will send you a preview to be confirmed.	

Unit : mm

